



## QINEO WDA-40

### Strong 4-roller wire drive unit for automated welding

The robust wire drive unit is designed for automated application. It has a stable, protective housing that accommodates the drive motor as well as its controller and power transmission mechanics. The precise 4-quadrant controller and high motor power ensure optimum traction and accuracy of the wire feed. Large roller diameters give the wire drive a high traction. This guarantees optimum ignition properties and a consistently high weld quality.

- Excellent welding results due to a powerful and slip-free wire feed
- Precise motor controller ensures optimum ignition properties and a stable arc
- High-quality components guarantee maximum availability
- Stable metal housing protects all relevant parts from external influences





# QINEO WDA-40

| Technical Data    |                     |
|-------------------|---------------------|
| Construction form | External wire drive |
| Wire feed speed   | max. 24 m/min       |
| Dimensions L/W/H  | 350/270/230 mm      |
| Weight            | 8.3 kg              |
| Wire diameter     | 0.8 - 2.0 mm        |

| Application |
|-------------|
| Auto        |

| Process   |
|---|
| <ul style="list-style-type: none"><li>• MIG/MAG Tandem welding</li><li>• MIG/MAG singel wire Pulse</li><li>• MIG/MAG singel wire AC</li><li>• MIG/MAG singel wire</li><li>• MIG Brazing</li></ul> |

## Questions about the product?

Your contact partner:  
Daniel Weber  
Tel.: +49 (0)2773 85-430  
gt-sales@cloos.de

