



QINEO GL 302 DC

TIG DC welding power source up to 290 ampere for manual welding

With their excellent price and performance ratio and their outstanding process functions you can use the QINEO GL-302 TIG Inverter welding power source for a wide range of applications. The welding power source is perfectly suited for on-site applications and repair welding in workshops. The high tolerance to mains voltage fluctuations guarantees best welding results with long cable lengths and when operating on a generator. Equipped as standard for gas-cooled TIG welding torches, the units can optionally be equipped with a cooling module. A trolley and a gas bottle holder are also available for an optimum mobility.

- Excellent price and performance ratio
- Safe arc ignition: Matched start parameters for best ignition conditions
- Suitable for MMA welding: Optimum flow behaviour and more protection due to VoltageReduceControl
- Optimum power and weight ratio The powerful but light partner - everywhere
- Everything at a glance: A clear operating panel for easy handling
- Robust construction: High level of stability of the devices





QINEO GL 302 DC

Technical Data

Welding current	5 A - 300 A
Welding current 100% duty cycl	210 A
Open circuit voltage	76 V
Mains voltage	400V / 50Hz / 3 phases
Connection cable	4 x 2,5 mm ²
Type of protection	IP 23 S
Dimensions (L/W/H) compact uni	460 x 230 x 325 mm
Weight compact unit	19.9 kg

Application

Manual

Process

- TIG DC welding

Questions about the product?

Your contact partner:
Daniel Weber
Tel.: +49 (0)2773 85-430
gt-sales@cloos.de



Technical modifications reserved
Version: 20.05.2024

CLOOS